

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

-.-

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
A		CREATION	28-NOV-18	GL	-

Adjustable on site *
Ajustable sur site

M10 Bolts stainless steel A2: 37Nm
Boulons M10 acier inoxydable A2: 37Nm

Dimensions: $\varnothing 32.6 - 34.5$, 152, 104, 45°, 16, 100, 175

360°

No scale
Sans échelle

M10 Bolts stainless steel A2: 37Nm *
Boulons M10 acier inoxydable A2: 37Nm

Dimensions: 27.8, 44.4, 100, 44.4, 200, $\varnothing 14.3$

*
In case of loosening, contact surfaces must be cleaned and greased
Refer to installation instruction

En cas de desserrage, les surfaces de contact doivent être nettoyées et graissées
Se référer à la notice d'installation

ITEM: 5.5

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	28-NOV-18		STE TE Connectivity	
		CHK	-			
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	NAME	
		0 PLC ± -		-		ADJUSTABLE PAD CONNECTOR FOR TWIN CONDUCTORS RACCORD ORIENTABLE A PLAGE POUR FAISCEAU DOUBLE
		1 PLC ± -		-		
		2 PLC ± -		PRODUCT SPEC		5 PDA 45 82 F M345 E200 100 C290
		3 PLC ± -		108-69096-001		
		4 PLC ± -		APPLICATION SPEC		SIZE
		ANGLES ± -		-		CAGE CODE
MATERIAL		FINISH		APPROX. WEIGHT		DRAWING NO
-		-		2.8 kg		A300779
				CUSTOMER DRAWING		RESTRICTED TO
				SCALE		1:3
				SHEET		1 OF 1
				REV		A

1470-19 (1/15)