



Technical Data

Highest Voltage U_m	KV	145
Lightning Impulse Voltage	kV	650
Length	mm	1926
Diameter over sheds (approx.)	mm	≤ 366
Flashover Distance	mm	1430
Creepage Distance (approx.)	mm	4590
Max. Conductor Size Cu/AL (approx.)	mm ²	1200
Outer Diameter Cable Insulation	mm	≤ 78
Outer Diameter Cable Oversheath	mm	≤ 130

DWN	16APR2019	MATERIAL	-	HEAT TREAT	-
MRI	16APR2019	CHK	THK		
APVD	16APR2019	ALE			
NAME: OHVT-145FS DRY FLEXIBLE TERMINATION 145KV					
SCALE	1:5	SIZE	A2	DRAWING NO	EPD-204-2011-00
			SHEET	1	OF 1
			REV	-	

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
mm		0 PLC	±
		1 PLC	±
		2 PLC	±
		3 PLC	±
		4 PLC	±
ANGLES:			
SURFACE TEXTURE		√	

LTR	REVISION RECORD	DATE	DWN	APVD

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TE CONNECTIVITY LTD. AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES (TE). IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN TE PERSONNEL, WITHOUT AUTHORIZATION FROM TE (www.te.com).

©2017 TE Connectivity Ltd. family of companies. All Rights Reserved